

Corrosion Resistant Aluminium Scaffolding Plank For Support Construction

Basic Information

. Place of Origin: China . Brand Name: bythai SGS,ISO · Certification: BT204 Model Number: • Minimum Order Quantity: 1000 • Price: 4.5-8.5 · Packaging Details: container • Delivery Time: 10-15 Payment Terms: L/C, T/T



Product Specification

• Features: High Strength, Durable

Color: Brown
Edge: Smooth
Length: 2m
Package: Pallet
Shape: Rectangle
Surface: Smooth
Thickness: 38mm

Treatment: Anti-corrosion Usage: Scaffolding

• Highlight: Aluminium Scaffolding Plank,

Corrosion Resistant Scaffolding Plank, Construction Support Scaffolding Plank



More Images



Product Description

Aluminium plank

Product Details

1. Characteristics of hot-dip galvanized materials:

Corrosion resistance: Hot-dip galvanizing can effectively resist moisture in the air and other corrosive media, extending the service life of the product.

I High strength: hot-dip galvanizing is firmly combined with

the steel matrix, improving the product's load-bearing capacity.

I Beautiful and durable: Hot-dip galvanized has a smooth surface, beautiful appearance and not easy to rust, maintaining a good appearance of the product.

2: Hook design

The hooked scaffolding steel plate has a unique design. The hook is made of strong steel. The installation method is flexible and diverse. It can easily connect multiple scaffolding steel plates and improve the construction efficiency. The steel plate without hook is suitable for occasions with higher load-bearing capacity, and the two can be used in conjunction with each other.

3: Customized service

Customization services can be provided according to customer needs, including customization in size, surface treatment and hook design. At the same time, we can also provide technical support and after-sales service to ensure that customers can use scaffolding

4: Transportation and storage

Transportation: Use containers for shipping to ensure that products will not be squeezed or collided during transportation. Aluminium plank

Specification	Width(inch)	Length(ft)	Hook(mm)	Weight(kg)
19*3	19.25	3	43/50	14.5
19*4	19.25	4	43/50	18.2
19*5	19.25	5	43/50	21.8
19*6	19.25	6	43/50	25.4
19*7	19.25	7	43/50	29.1
19*8	19.25	8	43/50	32.7
19*9	19.25	9	43/50	36.3
19*10	19.25	10	43/50	39.9





Durable material: Made of high-quality steel, specially treated to have good corrosion resistance and wear resistance, able to withstand long-term use and repeated loads.

Anti-slip design: The surface of the pedal adopts anti-slip texture or tooth-like design, which effectively improves the stability and safety of workers when standing and reduces the risk of accidental slipping.

Wide applicability: The pedals are standardized in size and can be used with scaffolding frames of various specifications and are suitable for scaffolding systems of different types and sizes.

Easy to install: The design is simple, and the installation is convenient and fast. No professional tools are required, and a safe and reliable scaffolding platform can be quickly built.

Multifunctional application: In addition to serving as a standing platform for scaffolding, it can also be used to build temporary working platforms, cargo storage areas, etc., to improve construction efficiency and space utilization. Applicable scene:

Construction sites: Suitable for various high-altitude operations on construction sites, such as wall building, painting, etc. Decoration project: As a temporary working platform during decoration construction, it facilitates the operation and movement of construction workers.



Bythai Scaffolding Co.,Ltd



17300780862



info@bythaiscaffolding.com



bythaiscaffold.com

No. 605, Industrail Exchange Center, Huanghua Town Changsha Hunan China